Scheda X- 01/12/202:





KUBE



ESPRESSO GROUP SERIES 700A INTEGRATED MOTOR 24 VDC



ESPRESSO GROUP SERIES 700E EXTERNAL MOTOR 230 V AC or 24 VDC

Kube is an innovative espresso coffee brewer that produces a superb cream within a neat, compact, and practical unit.

The versatile infusion capacity (up to 14gr of ground coffee) and the bi-directional hydraulic delivery make Kube a unique brewer of its kind.

TYPICAL APPLICATIONS

- Hot beverage vending machines
- Coffee machines

FEATURES AND BENEFITS

- Capacity of coffee doses from 6gr to 14gr (depending on version)
- Reverse hydraulic flow option gaining 70mm height recovery in machine layout
- Integrated 24VDC or external AC or DC motorization
- Mechanical positioning phases controlled by microswitches
- Compactness and mounting versatility in different configurations (front, left, right) depending on version
- Easy to remove and install
- Possibility of washing with hot water and / or in the dishwasher as it is free from electrical parts
- Simplicity of maintenance

TECHNICAL AND ELECTRICAL DATA

- Supply voltage 24 VDC (700A series) or 24 VDC / 230 V AC (700E series)
- Chamber capacity: from 6.5 to 9 gr (version \emptyset 37mm) or from 13 to 14 gr (version \emptyset 44mm)
- Recommended operating pressure 10 bar (+0.5 / -1)
- Operating ambient temperature 4 60°C
- Certified materials for food contact
- RoHS 2011/65/EU compliance and subsequent updates

For more information about versions, dimensions and other technical data contact our sales department.



FOOD CONTACT (MOCA) Regulation EC No 1935/2004 Regulation EC No 10/2011 Jation EC No 2023/2006 rials food on tested by

COMPONENTI VENDING S.P.A RESERVE RIGHT TO MODIFY THE PRESENT PRODUCT EVERY MOMENT AND WITHOUT NOTICE.

1 OF 1